



Référence	Capacité maxi à centre de charge	Longueur L1 / L2 / L3 (mm)	Fourreaux R (mm)	Section fourches S x T (mm)	H Hauteur (mm)	V Hauteur du crochet (mm)	U Largeur (mm)	CDG Centre de gravité mini / maxi (mm)	Poids (kg)
PETM*2500*2000	2500 kg à 500 mm	500 / 1200 / 2000	800	maxi 130 x 50	360	60	800	490 / 630	138
PETM*2500*2400		500 / 1400 / 2400	1200					550 / 730	152
PETM*2500*3000		500 / 1800 / 3000						720 / 950	176
PETM*2500*3600		500 / 2200 / 3600						870 / 1170	200
PETM*3200*2000	3200 kg à 500 mm	500 / 1200 / 2000	800	maxi 150 x 50	370	30	800	500 / 700	150
PETM*3200*2400		500 / 1400 / 2400	1200					600 / 800	165
PETM*3200*3000		500 / 1800 / 3000						770 / 1020	210
PETM*3200*3600		500 / 2200 / 3600						920 / 1275	240
PETM*5000*2000	5000 kg à 500 mm	500 / 1200 / 2000	800	maxi 150 x 60	480	40	800	530 / 700	220
PETM*5000*2400		500 / 1400 / 2400	1200					600 / 830	236
PETM*5000*3000		500 / 1800 / 3000						790 / 1070	300
PETM*5000*3600		500 / 2200 / 3600						940 / 1280	335
PETM*6000*2000	6000 kg à 600 mm	600 / 1200 / 2000	800	maxi 150 x 70	500	25	800	510 / 700	290
PETM*6000*2400		600 / 1400 / 2400	1200					600 / 830	320
PETM*6000*3000		600 / 1800 / 3000						780 / 1070	410
PETM*6000*3600		600 / 2200 / 3600						920 / 1300	460
PETM*8000*2000	8000 kg à 600 mm	600 / 1200 / 2000	800	maxi 180 x 70	600	120	850	520 / 700	355
PETM*8000*2400		600 / 1400 / 2400	1200					600 / 830	382
PETM*8000*3000		600 / 1800 / 3000						790 / 1100	470
PETM*8000*3600		600 / 2200 / 3600						920 / 1260	540

Livré avec un crochet réglable manuellement sur plusieurs positions.

Option = crochets supplémentaires.

Pour toutes demandes, nous consulter.